

**UNIFIED COMMUNICATIONS****INFORMATION**

## Stylish and discreet Professional 4K Webcam with Built in microphone, 5x Digital zoom, 120° field of view (FoV) and Auto Tracking



This stylish, professional 4K webcam with 5x Digital Zoom and built in microphone will take your video conferences to the new level. With a 120° field of view and 5x zoom, the UC-CAM10PRO-1 provides a sensational, smooth, and detailed picture. The webcam has two built-in microphones that detect sound from up to 4 meters away, so you can be sure everyone will be heard during the meetings. This compact-size camera with a privacy cover will be a perfect match for any space - whether it's a small huddle space or meeting room. With a 14° tilt adjustment feature, the camera can be customized to fit your needs and adapt to your individual space.



### 120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.



### 2D & 3D Digital Noise Reduction

Delivering high image quality, these two image denoising technologies combined ensure crisp and clear visuals for video and photos.



### Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.



### Clear, crisp and natural audio

Featuring an advanced noise reduction algorithm, the integrated 2-element mic array detects audio from up to 4 metres away, delivering high quality audio free from any annoying background noise or distortion.

## SPECIFICATION

### 01 CAMERA

<b>Pixels</b>	8,46M
<b>Native resolution</b>	4K UHD
<b>Supported resolutions</b>	2160p/30fps, 1440p/30fps, 1080p/30fps
<b>Diagonal field of view (dFoV)</b>	120°
<b>Focus mode</b>	fixed
<b>Focus distance</b>	8m
<b>Aperture</b>	2.5
<b>Zoom</b>	5x digital zoom
<b>White balance</b>	yes
<b>Exposure</b>	yes
<b>Backlight compensation</b>	yes
<b>AutoFraming</b>	yes

### 02 AUDIO

<b>Number of microphone arrays</b>	2
<b>Voice pickup distance</b>	4m
<b>Voice pickup angle</b>	180°
<b>Noise reduction</b>	yes
<b>Automatic gain control</b>	yes

### 03 CONNECTIVITY

<b>Camera</b>	USB Type-C
<b>Host</b>	USB v.3.0

### 04 MICROPHONE

<b>Number of microphone arrays</b>	x2
<b>Voice pickup range</b>	4m (radius)

### 05 CONNECTIVITY & BUTTON OPERATIONS

**USB Type C** x1

### 06 MECHANICAL

<b>Tilt angle</b>	≤14°
<b>Rotation</b>	360°
<b>Privacy shutter</b>	yes

## 07 ACCESSORIES INCLUDED


<b>Cables</b>	USB 2.0 (type A to C)
<b>Anti peeping cover</b>	yes
<b>Remote control</b>	yes (batteries included)
<b>Power adapter</b>	yes

## 08 SUSTAINABILITY

**Regulations** CE, RoHS support, ErP, WEEE, REACH, UKCA

## 09 DIMENSIONS / WEIGHT

<b>Product dimensions</b> W x H x D	80 x 75 x 53mm
<b>Box dimensions W x</b> <b>H x D</b>	162 x 124 x 90mm
<b>Weight (without box)</b>	0.21kg
<b>Weight (with box)</b>	0.5kg
<b>EAN code</b>	4948570033140



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IYAMA CORPORATION. ALL RIGHTS RESERVED