

ProLite E2607WS-1

The new 'flagship' product from iiyama is the E2607WS, a High Definition, 2msec 26" LCD solution perfect for today's demanding applications. Superb colour quality is achieved by a 1000:1 contrast ratio and the option to enhance colour further by enabling Advanced Contrast Ratio. The 'OptiColour' features allows quick and simple adjustment of the colour settings to suit the application or mood. 5 Watt speakers offer Stereo Audio performance well above the average multimedia display available today. The three input configuration of HDMI, DVI and Analogue guarantees compatibility with the flexibility to switch between multiple sources.



Panel	TN
Diagonal	26"
Display area h x w	343.8 x 550.1 mm; 13.54" x 21.66"
Response time	2 ms
Contrast	4000 : 1 ACR
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 170°/150°; right/left: 85°/85°; up/down: 80°/70°
Viewing zone CR>5	horizontal/vertical: 178°/170°; right/left: 89°/89°; up/down: 85°/85°
Display colour	16.7 million
Pixel pitch h x v	0.2865 x 0.2865 mm
Native resolution	1920 x 1200 (2.3 megapixel)
Horizontal sync	31 - 80 KHz
Vertical sync	56 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D, HDMI
Synchronization	Separate Sync
Plug & Play	VESA DDC 1/2B™
Speakers	2 x 5 W (Stereo)
Included accessories	Power Cable, D-Sub Cable, DVI-D Cable, Audio cable, user manual, stand
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, FR, DE, ES, IT, FIN, Chinese (simplified and traditional) and 5 front controls (Menu/Input Select, Scroll down/Brightness/Contrast/ACR/ECO, Scroll up/OptiColour Mode, Select/Input Select, Power)
User controls	auto adjust, contrast, brightness, ACR, ECO, input select, audio adjust, colour adjust, information, manual image adjust (horizontal size, H/V position, fine tune, sharpness, video mode adjust, OptiColour mode), setup menu (language select, OSD position, OSD time out), memory recall
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Safety	CE, TUV/Baurt, VCCI-B, FCC
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	52 W typical; max. 2 W in Power management mode
Power management	VESA DPMS
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	200 x 100 mm
Tilt angle	20° up
Dimensions w x h x d	597.5 x 460.5 x 238 mm
Weight	8.3 kg
Aspect ratio	16 : 10
Price	£ 279 SRP ex VAT

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.