

# ProLite E2607WS-1

The new 'flagship' product from iiyama is the E2607WS, a High Definition, 2msec 26" LCD solution perfect for today's demanding applications. Superb colour quality is achieved by a 1000:1 contrast ratio and the option to enhance colour further by enabling Advanced Contrast Ratio. The 'OptiColour' features allows quick and simple adjustment of the colour settings to suit the application or mood. 5 Watt speakers offer Stereo Audio performance well above the average multimedia display available today. The three input configuration of HDMI, DVI and Analogue guarantees compatibility with the flexibility to switch between multiple sources.



|                         |   |
|-------------------------|---|
| Panel                   | TN  |
| Diagonal                | 26"   |
| Display area h x w      | 343.8 x 550.1 mm; 13.54" x 21.66"   |
| Response time           | 2 ms  |
| Contrast                | 4000 : 1 ACR  |
| Brightness              | 300 cd/m <sup>2</sup> typical   |
| Viewing zone            | horizontal/vertical: 170°/150°; right/left: 85°/85°; up/down: 80°/70°   |
| Display colour          | 16.7 million  |
| Pixel pitch h x v       | 0.2865 x 0.2865 mm  |
| Native resolution       | 1920 x 1200 (2.3 megapixel)   |
| Horizontal sync         | 31 - 80 KHz   |
| Vertical sync           | 56 - 75 Hz  |
| Analog input connector  | D-Sub   |
| Digital input connector | DVI-D, HDMI   |
| Synchronization         | Separate Sync   |
| Plug & Play             | VESA DDC 1/2B™  |
| Speakers                | 2 x 5 W (Stereo)  |
| Included accessories    | Power Cable, D-Sub Cable, DVI-D Cable, Audio cable, user manual, stand  |
| Apple - Mac             | All iiyama monitors are compatible with Apple-Macintosh computers.  |
| Controls                | Via OSD in 9 languages (EN, FR, DE, ES, IT, FIN, Chinese (simplified and traditional) and 5 front controls (Menu/Input Select, Scroll down/Brightness/Contrast/ACR/ECO, Scroll up/OptiColour Mode, Select/Input Select, Power)  |
| User controls           | auto adjust, contrast, brightness, ACR, ECO, input select, audio adjust, colour adjust, information, manual image adjust (horizontal size, H/V position, fine tune, sharpness, video mode adjust, OptiColour mode), setup menu (language select, OSD position, OSD time out), memory recall |
| Driver                  | Windows 95 / 98 / 2000 / ME / XP / Vista  |
| Safety                  | CE, TUV/Baurt, VCCI-B, FCC  |
| Power supply            | AC 100 - 240 V, 50 / 60 Hz  |
| Power Supply Unit       | internal  |
| Power usage             | 52 W typical; max. 2 W in Power management mode   |
| Power management        | VESA DPMS   |
| Anti-theft-device       | Kensington-lock™ prepared   |
| VESA mounting           | 200 x 100 mm  |
| Tilt angle              | 20° up  |
| Dimensions w x h x d    | 597.5 x 460.5 x 238 mm  |
| Weight                  | 8.3 kg  |
| Aspect ratio            | 16 : 10   |
| Price                   | £ 279 SRP ex VAT  |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.