

ProLite E1908WSV-1

The ProLite E1908WSV widescreen monitor with high resolution 1680x1050 panel features a rapid 5msec response time, ideal for games and videos. Superb colour quality is achieved by a 1000:1 contrast ratio and the option to enhance colour further by enabling Dynamic Contrast Ratio (5000:1). Higher than average brightness and built-in speakers offer an enriched multimedia experience. This model is available in black and silver.



Panel	TN
Diagonal	19"
Display area h x w	255.15 x 408.24 mm
Response time	5 ms
Contrast ratio	1000 : 1 typical
Contrast ratio	5000 : 1 DCR
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.243 x 0.243 mm
Native resolution	1680 x 1050 (1.8 megapixel)
Horizontal sync	31 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, audio cable, user manual, stand
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 6 languages (EN, DE, FR, ES, IT, JP) and 5 front controls (Power, Menu, + Button, - Button, Auto)
User controls	brightness, contrast, clock, phase, V-position, H-position, auto adjust, colour temperature, sharpness, gamma, economy mode, OSD position, OSD time off, OSD language, picture mode, volume, full screen, DCR, reset
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TÜV-Ergonomics
Safety	CE, TÜV-GS
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	38 W typical; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	439 x 365 x 190 mm
Weight	3.7 kg
Aspect ratio	16 : 10
Price	£ 109 SRP ex VAT

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.