

ProLite E2008HDS-1

The iiyama E2008HDS-1 20" LCD offers great value for money, and is the ideal screen for Gaming or as a Home Office display. iiyama's Opti-Colour Modes ensure high colour performance, supported by an ultra fast 2msec response time and a high 1600 x 900 resolution. With DVI and VGA connections and iiyama's new Power Saving Eco Modes, you are in safe hands with this superb display.



Panel	TN
Diagonal	20"
Display area h x w	249.1 x 442.8 mm; 9.8" x 17.4"
Response time	2 ms
Contrast	30 000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	250 cd/m ² typical
Viewing zone	horizontal/vertical: 160°/160°; right/left: 80°/80°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.2768 x 0.2768 mm
Native resolution	1600 x 900 (1.44 megapixel)
Horizontal sync	31 - 83 KHz
Vertical sync	56 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D
HDCP	yes
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D cable, Audio cable, quick start guide, stand
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 10 languages (EN, FR, DE, IT, PL, ESP, NL, JP, Chinese, RU) and 6 front controls (Power, Menu /Select, Scroll up /Brightness, Scroll down /ECO, Exit /OptiColour, Auto)
User controls	auto adjust, brightness, contrast, geometry (H. position, V. position, pixel clock, phase), colour, OSD (H. position, V. position, OSD Time out), language, miscellaneous (sharpness, DDC/CI, display information, ACR, display mode, OD), input select, audio (volume, mute), recall
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Safety	CE, TÜV-Bauart, VCCI-B
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	25 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, Energy Star®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	485 x 367 x 193 mm
Weight	4 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.