

ProLite T2250MTS-1

The ProLite T2250MTS 22" Touch Screen is an early adaptor of the new 'MultiTouch' Technology. Based on the latest Optical sensor, the T2250MTS is Windows® 7 Compatible and ready for the emerging business and consumer software packages. The innovative T2250MTS lets you browse the web, email and draw while working on multiple screens, docking and or typing on the on-screen keyboard. You can scroll and rotate pictures, draw, zoom in and out using certain tap, flick, grab and pincer gestures. The multi-touch is not only fast but also fun to work with. The panel features High Definition 1920 x 1080 resolution with a 5msec response time. Analogue and DVI inputs are available for flexible connectivity along with USB for the Touch Interface.



| | |
|-------------------------|---|
| Panel | TN |
| Diagonal | 22" |
| Touchtechnology | optical, multitouch (2 compatible touch points), activated by finger or stylus |
| Light transmittance | 88% |
| Display area h x w | 268.11 x 476.64 mm; 10.6" x 18.8" |
| Response time | 5 ms |
| Contrast | 1000 : 1 typical |
| Brightness | 260 cd/m ² typical |
| Viewing zone | horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 85°/75° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.248 x 0.248 mm |
| Native resolution | Full HD 1080p, 1920 x 1080 (2.1 megapixel) |
| Horizontal sync | 31 - 82 KHz |
| Vertical sync | 56 - 75 Hz |
| Analog input connector | D-Sub |
| Digital input connector | DVI-D |
| HDCP | yes |
| Interface | USB |
| Synchronization | Separate Sync |
| Plug & Play | VESA DDC2B™ |
| Speakers | 2 x 1 W (Stereo) |
| Included accessories | power cable, D-Sub cable, DVI-D cable, audio cable, USB cable, stand, stylus, quick start guide |
| Controls | On-Screen-Display in 8 languages (EN, FR, DE, IT, JP, PL, NL, RU) and 5 front controls (Power, Auto, Scroll up/ Brightness/ Contrast, Scroll down/ Volume, Meu/ Select) |
| User controls | brightness, contrast, image control (auto adjust, H. position, V. position, clock, phase, sharpness), colour adjust, OSD control (H. position, V. position, timeout), other (language, input, speaker volume, information), reset, exit |
| Driver | Windows® 7 |
| Safety | CE, TÜV/Bauart, VCCI-B |
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power management | VESA DPMS |
| Power usage | 44 W typical; max. 1 W in Power management mode |
| Anti-theft-device | Kensington-lock™ prepared |
| VESA mounting | 100 mm |
| Tilt angle | 20° up; 3° down |
| Dimensions w x h x d | 513 x 419 x 263 mm |
| Weight | 6 kg |
| Aspect ratio | 16 : 9 |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.