

ProLite E2201W-2

Ideal for home or office applications the ProLite E2201W-2 wide screen LCD is a ground breaking product and this latest specification features improved Dynamic Contrast Ratio of 3000:1. This leading technology produces superb depth of colour suitable for photographic and digital print environments. A rapid 2msec response time makes the E2201W-2 ideal for gaming and video applications. The monitor has digital and analogue inputs and is available in black.



Panel	TN
Diagonal	22"
Display area h x w	296.1 x 473.8 mm
Response time	2 ms
Contrast	3000 : 1 DCR
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.282 x 0.282 mm
Native resolution	1680 x 1050 (1.8 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Bandwidth	162 MHz
Analog input connector	D-Sub
Digital input connector	DVI-D
HDCP	yes
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Included accessories	power cable, D-Sub signal cable, DVI-D signal cable, user manual, stand, cable holder
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 6 languages (GB, F, D, I, ESP, JP) and 6 Front controls (Power, Menu, + Button, - Button, Auto, Input)
User controls	brightness, contrast, clock, phase, V-position, H-position, colour temperature, auto set-up, sharpness, gamma, economy mode, OSD language, OSD position, OSD time out, signal select, reset
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TCO '03, TÜV-Ergonomics
Safety	TÜV GS, FCC-B, UL / C-UL, CE, VCCI-B, GOST-R, CCC
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	max. 49 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	507 x 410.5 x 209.5 mm
Weight	5.8 kg
Aspect ratio	16 : 10
Price	£ 149 SRP ex VAT

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.