

# ProLite E1908WSV-1

The ProLite E1908WSV widescreen monitor with high resolution 1680x1050 panel features a rapid 5msec response time, ideal for games and videos. Superb colour quality is achieved by a 1000:1 contrast ratio and the option to enhance colour further by enabling Dynamic Contrast Ratio (5000:1). Higher than average brightness and built-in speakers offer an enriched multimedia experience. This model is available in black and silver.



|                        |                                                                                                                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Panel                  | TN                                                                                                                                                                                                                   |
| Diagonal               | 19"                                                                                                                                                                                                                  |
| Display area h x w     | 255.15 x 408.24 mm; 10" x 16.1"                                                                                                                                                                                      |
| Response time          | 5 ms                                                                                                                                                                                                                 |
| Contrast               | 1000 : 1 typical                                                                                                                                                                                                     |
| Contrast               | 5000 : 1 DCR                                                                                                                                                                                                         |
| Brightness             | 300 cd/m <sup>2</sup> typical                                                                                                                                                                                        |
| Viewing zone           | horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°                                                                                                                                                |
| Display colour         | 16.7 million                                                                                                                                                                                                         |
| Pixel pitch h x v      | 0.243 x 0.243 mm                                                                                                                                                                                                     |
| Native resolution      | 1680 x 1050 (1.8 megapixel)                                                                                                                                                                                          |
| Horizontal sync        | 31 - 80 KHz                                                                                                                                                                                                          |
| Vertical sync          | 55 - 75 Hz                                                                                                                                                                                                           |
| Analog input connector | D-Sub                                                                                                                                                                                                                |
| Synchronization        | Separate Sync                                                                                                                                                                                                        |
| Plug & Play            | VESA DDC2B™                                                                                                                                                                                                          |
| Speakers               | 2 x 1 W (Stereo)                                                                                                                                                                                                     |
| Included accessories   | power cable, D-Sub cable, audio cable, user manual, stand                                                                                                                                                            |
| Apple - Mac            | All iiyama monitors are compatible with Apple-Macintosh computers.                                                                                                                                                   |
| Controls               | Via OSD in 6 languages (EN, DE, FR, ES, IT, JP) and 5 front controls (Power, Menu, + Button, - Button, Auto)                                                                                                         |
| User controls          | brightness, contrast, clock, phase, V-position, H-position, auto adjust, colour temperature, sharpness, gamma, economy mode, OSD position, OSD time off, OSD language, picture mode, volume, full screen, DCR, reset |
| Driver                 | Windows 95 / 98 / 2000 / ME / XP / Vista                                                                                                                                                                             |
| Ergonomics             | TÜV-Ergonomics                                                                                                                                                                                                       |
| Safety                 | CE, TÜV-GS                                                                                                                                                                                                           |
| Power supply           | AC 100 - 240 V, 50 / 60 Hz                                                                                                                                                                                           |
| Power Supply Unit      | internal                                                                                                                                                                                                             |
| Power usage            | 38 W typical; max. 2 W in Power management mode                                                                                                                                                                      |
| Power management       | VESA DPMS, ENERGY STAR®                                                                                                                                                                                              |
| Anti-theft-device      | Kensington-lock™ prepared                                                                                                                                                                                            |
| VESA mounting          | 100 mm                                                                                                                                                                                                               |
| Tilt angle             | 20° up; 5° down                                                                                                                                                                                                      |
| Dimensions w x h x d   | 439 x 365 x 190 mm                                                                                                                                                                                                   |
| Weight                 | 3.7 kg                                                                                                                                                                                                               |
| Aspect ratio           | 16 : 10                                                                                                                                                                                                              |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.