

ProLite E2003WSV-1

iiyama's most recent addition to the widescreen monitor portfolio, the E2003WSV 20.1" panel is aimed at the user who appreciates the higher 1680x1050 screen resolution but lacks space for a 22". Improved features include an even faster 2ms response time for excellent results in gaming and video playback, increased brightness of 300 cd/m² and a sharp 2000:1 Dynamic Contrast Ratio delivering crisp, vivid images in any application. The smart black casing incorporates stereo speakers and the access controls for the On Screen Display Menu.



| | |
|------------------------|---|
| Panel | TN |
| Diagonal | 20" |
| Display area h x w | 270.9 x 433.4 mm |
| Response time | 2 ms |
| Contrast | 2000 : 1 DCR |
| Brightness | 300 cd/m ² typical |
| Viewing zone | horizontal/vertical: 170°/170°; right/left: 85°/85°; up/down: 85°/85° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.258 x 0.258 mm |
| Native resolution | 1680 x 1050 (1,8 megapixel) |
| Horizontal sync | 31 - 83 KHz |
| Vertical sync | 56 - 75 Hz |
| Bandwidth | 165 MHz |
| Analog input connector | D-Sub |
| Output connector | headphone socket |
| Synchronization | Separate Sync |
| Plug & Play | VESA DDC2B™ |
| Speakers | 2 x 1 W (Stereo) |
| Included accessories | power cable, D-Sub signal cable, audio cable, user manual, stand |
| Apple - Mac | All iiyama monitors are compatible with Apple-Macintosh computers. |
| Controls | On-Screen-Display in 10 languages (GB, F, D, I, ESP, JP, NL, PL, RU, CH) and 6 Front controls (Auto, Exit/Volume, Scroll down/Contrast, Scroll up/Brightness, Menu/Select, Power) |
| User controls | auto adjust, luminance (brightness, contrast), geometry (clock, phase, V-position, H-position), colour temperature, OSD language, OSD position, OSD time out, recall, miscellaneous (sharpness, DDC/CI, display information, DCR, OD), volume |
| Driver | Windows 95 / 98 / 2000 / ME / XP / Vista |
| Ergonomics | TCO '03, CE, MPR 3 (prEN50279), ISO 13406-2 |
| Safety | TÜV GS, FCC-B, UL / C-UL, VCCI-B, GOST-R, CB |
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power usage | max. 49 W in normal use; max. 2 W in Power management mode |
| Power management | VESA DPMS, ENERGY STAR® |
| Anti-theft-device | Kensington-lock™ prepared |
| VESA mounting | 100 mm |
| Tilt angle | 22° up; 2° down |
| Dimensions w x h x d | 480 x 399 x 188 mm |
| Weight | 4.4 kg |
| Aspect ratio | 16 : 10 |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.