

ProLite T1530SR-1

ProLite T1530SR is based on the latest 5 Wire Resistive technology. Price / performance ratio is ideal for the budget conscious user while quality and specification is certainly not compromised. The display inputs include both Analogue and Digital (DVI) with Touchscreen connectivity via either USB or RS-232 which offers greater than typical flexibility. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree angles. Extensive Touch Utilities allow for 4 point calibration and either 9/25 point linerization. An incredibly powerful Touch solution.



Panel	TN
LCD type	digital, colour TFT-LCD (active)
Diagonal	15"
Touchtechnology	resistive
Light transmittance	80%
Display area h x w	228.1 x 304.1 mm
Response time	16 ms
Contrast ratio	500 : 1 with touch panel
Brightness	280 cd/m ² with touch panel
Viewing zone	horizontal/vertical: 120°/100°; right/left: 60°/60°; up/down: 40/60°
Display colour	16.2 million
Pixel pitch h x v	0.297 x 0.297 mm
Native resolution	1024 x 768 (0.8 megapixel)
Horizontal sync	31 - 60 KHz
Vertical sync	60 - 75 Hz
Bandwidth	80 MHz
Analog input connector	D-Sub
Digital input connector	DVI-D
Interface	RS-232C, USB
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	AC adapter, power cable, D-Sub signal cable, DVI-D signal cable, RS-232C signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), user manual
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 7 languages (D, GB, ESP, F, I, JP, Chinese) and 5 Front controls (Menu, Brightness, Volume, Input, Power)
User controls	contrast, brightness, volume, auto set-up, V-position, H-position, OSD language, clock, phase, colour temperature, signal select, reset
Driver	Windows (Vista, XP, 9X, 2000, CE, NT4), Linux, Mac, DOS
Safety	CE, TÜV-SUD, FCC-B, UL / C-UL, VCCI-B, CB
Power supply	DC12V, 4A
Power Supply Unit	external
Power usage	max. 23 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS
VESA mounting	75 mm
Tilt angle	90° up; 5° down
Dimensions w x h x d	351 x 314.5 x 140 mm
Weight	4.3 kg
Aspect ratio	4 : 3

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.