

# ProLite E1902S-1

An ultra fast 2 millisecond response time coupled with a sleek and stylish black cabinet ensures that iiyama's new 19-inch ProLite E1902S brings a host of advance features to your fingertips at an affordable price. The monitor delivers a sharp 1000:1 contrast ratio, 300cd/m<sup>2</sup> brightness and has one D-Sub and one DVI input.



Panel	TN
Diagonal	19"
Display area h x w	301.1 x 376.3 mm
Response time	2 ms
Contrast ratio	1000 : 1 typical
Brightness	300 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 160°/160°; right/left: 80°/80°; up/down: 80/80°
Viewing zone CR>5	horizontal/vertical: 170°/170°; right/left: 85°/85°; up/down: 85/85°
Display colour	16.7 million
Pixel pitch h x v	0.294 x 0.294 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Bandwidth	135 MHz
Analog input connector	D-Sub
Digital input connector	DVI-D
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D signal cable, audio cable, user manual, stand, cable holder
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 6 languages (D, GB, ESP, F, I, JP) and 5 Front controls(Menu, + Button (Volume+), Power, - Button (Volume -), Auto)
User controls	brightness, contrast, colour temperature, auto set-up, sharpness, gamma, economy mode, clock, phase, V-position, H-position, OSD language, OSD position, OSD time out, signal select, volume
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TCO '03, ISO 13406-2
Safety	TÜV GS, FCC-B, UL / C-UL, CE, VCCI-B, GOST-R, CCC
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	max. 42 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	407.5 x 407 x 210 mm
Weight	4.9 kg
Aspect ratio	5 : 4

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.