

ProLite B1902S-1

The new 'B' series of displays from iiyama means what it stands for - Business. The specification and features are impressive, offering superb picture quality and flexibility for Business applications. Height Adjustability is integrated into the base with a adjustment range of 110mm. At the heart of the PLB1902S is a high performance TN panel with a 1.3 megapixel resolution and powerful contrast / brightness partnership ensuring vibrant and vivid picture quality. Comprising of both Analogue and Digital inputs with free Digital cable compatibility with your system is assured. The PLB1902S is available in Black or Ivory.



Panel	TN
Diagonal	19"
Display area h x w	301.1 x 376.3 mm
Response time	2 ms
Contrast ratio	1000 : 1 typical
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 160°/160°; right/left: 80°/80°; up/down: 80/80°
Viewing zone CR>5	horizontal/vertical: 170°/170°; right/left: 85°/85°; up/down: 85/85°
Display colour	16.7 million
Pixel pitch h x v	0.294 x 0.294 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Bandwidth	135 MHz
Analog input connector	D-Sub
Digital input connector	DVI-D
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D signal cable, audio cable, user manual, cable holder
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 6 languages (D, GB, ESP, F, I, JP) and 5 Front controls(Menu, + Button (Volume+), Power, - Button (Volume -), Auto)
User controls	brightness, contrast, colour temperature, auto set-up, sharpness, gamma, economy mode, clock, phase, V-position, H-position, OSD language, OSD position, OSD time out, signal select, volume, reset
Driver	Windows 95 / 98 / 2000 / ME / XP
Ergonomics	TCO '03, ISO 13406-2
Safety	TÜV GS, FCC-B, UL / C-UL, CE, VCCI-B, GOST-R, CCC
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	max. 42 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Height adjustment	110 mm
Swivel Stand	70°; 35° left; 35° right
Tilt angle	25° up; 5° down
Dimensions w x h x d	407.5 x 393 (503) x 236.5 mm
Weight	6 kg
Aspect ratio	5 : 4

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.