

ProLite E2202WSV-1

Ideal for Home or Office applications the ProLite E2202WSV Wide Screen LCD is a ground breaking product. A 1000:1 contrast ratio produces remarkable depth of colour suitable for Photographic and Digital Print environments. A rapid 5msec response time makes the E2202WSV suitable for gaming and video applications. The ProLite E2202WSV has one Analogue input and is available in Black.



Panel	TN
Diagonal	22"
Display area h x w	290.6 x 464.9 mm
Response time	5 ms
Contrast ratio	1000 : 1 typical
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 160°/160°; right/left: 80°/80°; up/down: 80/80°
Display colour	16.7 million
Pixel pitch h x v	0.277 x 0.277 mm
Native resolution	1680 x 1050 (1.8 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Bandwidth	162 MHz
Analog input connector	D-Sub
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 2 W (Stereo)
Included accessories	power cable, D-Sub signal cable, audio cable, user manual, stand, cable holder
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 6 languages (GB, F, D, I, ESP, JP) and 5 Front controls (Power, Menu, + Button, - Button, Auto)
User controls	brightness, contrast, clock, phase, V-position, H-position, colour temperature, auto set-up, sharpness, gamma, economy mode, volume, OSD language, OSD position, OSD time out, reset
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TCO '03, TÜV-Ergonomics
Safety	TÜV GS, FCC-B, UL / C-UL, CE, VCCI-B
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	max. 56 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	506 x 404.5 x 210 mm
Weight	5 kg
Aspect ratio	16 : 10

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.