

# ProLite H511S-2

The 20.1" ProLite H511S offers plenty of area to display every element of even the most space-hungry applications. The PVA LCD technology provides a native resolution of 1600 x 1200 and a lateral viewing angle of 178°. The height of the display can be adjusted through 110mm and the screen itself rotates for a landscape or portrait viewing mode. Flexible inputs (1 x VGA & 1 x DVI-D with cables included) reinforces the position of the ProLite H511S as the professional 20.1" LCD of choice. Available in both ivory and black.



Panel	PVA
Diagonal	20.1"
Display area h x w	306 x 408 mm
Response time	8 ms
Contrast ratio	900 : 1 typical
Brightness	300 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 178°/178°; right/left: 89°/89°; up/down: 89/89°
Display colour	16.7 million
Pixel pitch h x v	0.255 x 0.255 mm
Native resolution	1600 x 1200 (1.9 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 85 Hz
Bandwidth	162 MHz
Analog input connector	D-Sub
Digital input connector	DVI-D
Output connector	headphone socket
Synchronization	Composite, Separate, Sync On Green
Plug & Play	DDC 2B™
Speakers	2 x 2 W (Stereo)
Included accessories	power Cable, D-Sub Cable, audio cable, user manual, Pivot® & Liquid view software
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	OSD menu - 6 languages (D, GB, F, SV, Jp, I), 6 control buttons (Power, Auto-Setup, brightness, contrast, menu, signal selection)
User controls	brightness, contrast, colour temperature, horizontal and vertical position, clock, phase, sharpness, regulation of basic colours, sRGB, gamma correction, Eco mode, signal input, OSD position, OSD Timer, OSD lock out, zoom (full screen, 1 : 1, max. preservation of the original ratio of dimensions), reset
Driver	Windows 95 / 98 / 2000 / ME / XP
Ergonomics	TCO'03 (ProLite H511S-B: TCO'99), MPR III (prEN50279), ISO 13406-2
Safety	CE, TÜV GS, FCC-B, UL/C-UL, VCCI-B, CCC
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	max. 55 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Height adjustment	110 mm
Rotation (pivot function)	90°
Swivel Stand	70°; 35° left; 35° right
Tilt angle	35° up; 5° down
Dimensions w x h x d	446 x 391.5 (501.5) x 242 mm
Weight	10 kg
Aspect ratio	4 : 3

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.