

ProLite B2403WS-1

The new iiyama flag ship 24" display is ideal for both the Home Enthusiast, Gamer and Business professional. The 1920 x 1200 pixel panel has the latest advancements in technology, boasting a 2000:1 Dynamic Contrast Ratio which can be disabled for greater colour accuracy and a 2msec response time ensuring the best possible video and animation playback with minimal blurring. Of course, the B2403 is full HD and incorporates the HDMI input for connectivity between DVD Players, Games Consoles and Graphics Cards choosing this interface type. A HDMI to DVI cable is now included as standard.



Panel	TN
Diagonal	24"
Display area h x w	324 x 518.4 mm
Response time	2 ms
Contrast	2000 : 1 DCR
Brightness	300 cd/m ² max.
Viewing zone	horizontal/vertical: 170°/170°; right/left: 85°/85°; up/down: 85°/85°
Display colour	16.7 million
Pixel pitch h x v	0.270 x 0.270 mm
Native resolution	1920 x 1200 (2.3 megapixel)
Horizontal sync	31 - 83 KHz
Vertical sync	56 - 75 Hz
Bandwidth	162 MHz
Analog input connector	D-Sub
Digital input connector	HDMI
HDCP	yes
Output connector	headphone socket
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 2 W (Stereo)
Included accessories	power cable, D-Sub signal cable, audio cable, user manual, DVI-HDMI Cable
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 10 languages (GB, F, D, I, ESP, PL, RU, JP, NL, Ch) and 6 Front controls(Auto, Exit/Volume Button, Scroll Down/Contrast Button, Scroll Up/Brightness Button, Menu/Select, Power).
User controls	brightness, contrast, colour adjust, auto adjust, geometry (horizontal/vertical position, pixel clock, phase), OSD language, OSD position, OSD time out, volume, input select, recall, miscellaneous (sharpness, DDC/CI, Display Information, DCR, OD, Display Mode)
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TCO'03, CE, MPR III (prEN50279), ISO13406-2
Safety	TÜV GS, FCC-B, UL/C-UL, VCCI-B, GOST-R, CB
Power supply	AC 100-240V, 50/60 Hz
Power Supply Unit	internal
Power usage	max. 65 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Height adjustment	130 mm
Rotation (pivot function)	90°
Swivel Stand	90°; 45° left; 45° right
Tilt angle	20° up; 5° down
Dimensions w x h x d	566 x 445 (575) x 220 mm
Weight	8.7 kg
Aspect ratio	16 : 10

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.