

ProLite E2403WS-1

The new E-Series 24" display is the latest pioneering product suitable for both Home, Gaming and Business environments. The 1920x1200 pixel panel has the latest TN technology and boasts a 2000:1 Dynamic Contrast Ratio which can be disabled for greater colour accuracy. A brightness of 300cd/m², an extremely fast 2ms response time, the E2403WS is ideal for movies or games plus it is now full HD and incorporates the HDMI input for multiple connectivity and all packaged in iiyama's trademark sleek and stylish design. A HDMI to DVI cable is now included as standard. The display has been tested to meet all of the technical requirements to be Certified for Windows Vista™.



Panel	TN
Diagonal	24"
Display area h x w	324 x 518.4 mm
Response time	2 ms
Contrast	2000 : 1 DCR
Brightness	300 cd/m ² max.
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 85°/75°
Display colour	16.7 million
Pixel pitch h x v	0.270 x 0.270 mm
Native resolution	1920 x 1200 (2.3 megapixel)
Horizontal sync	31 - 83 KHz
Vertical sync	56 - 75 Hz
Bandwidth	162 MHz
Analog input connector	D-Sub
Digital input connector	HDMI
HDCP	yes
Output connector	headphone socket
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 2 W (Stereo)
Included accessories	power cable, D-Sub signal cable, audio cable, user manual, DVI-HDMI Cable
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 10 languages (GB, F, D, I, ESP, PL, RU, JP, NL, Ch) and 6 Front controls(Auto, Exit/Volume Button, Scroll Down/Contrast Button, Scroll Up/Brightness Button, Menu/Select, Power).
User controls	brightness, contrast, colour adjust, auto adjust, geometry (horizontal/vertical position, pixel clock, phase), OSD language, OSD position, OSD time out, volume, input select, recall, miscellaneous (sharpness, DDC/CI, Display Information, DCR, OD, Display Mode)
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TCO'03, CE, MPR III (prEN50279), ISO13406-2
Safety	TÜV GS, FCC-B, UL/C-UL, VCCI-B, GOST-R, CB
Power supply	AC 100-240V, 50/60 Hz
Power Supply Unit	internal
Power usage	max. 65 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	566 x 458.5 x 191.5 mm
Weight	6.5 kg
Aspect ratio	16 : 10

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.