

ProLite E1702S-2

The 'E' series 17" LCD from iiyama is the monitor of choice for home and office applications. An impressive 5msec response time makes it ideal for watching movies on your PC or for the gaming enthusiast. Superb picture quality is assured by an impressive contrast ratio producing vibrant and vivid colours. The ProLite E1702S has both Analogue and Digital inputs for choice of connectivity.



Panel	TN
Diagonal	17"
Display area h x w	270.3 x 337.9 mm
Response time	5 ms
Contrast ratio	1000 : 1 typical
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 160°/160°; right/left: 80°/80°; up/down: 80/80°
Viewing zone CR>5	horizontal/vertical: 178°/178°; right/left: 89°/89°; up/down: 89/89°
Display colour	16.7 million
Pixel pitch h x v	0.264 x 0.264 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Bandwidth	135 MHz
Analog input connector	D-Sub
Digital input connector	DVI-D
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D signal cable, audio cable, user manual, cable holder, stand
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	On-Screen-Display in 6 languages (D, GB, ESP, F, I, JP) and 5 Front controls(Menu, + Button (Volume+), Power, - Button (Volume -), Auto)
User controls	brightness, contrast, clock, phase, V-position, H-position, colour temperature, auto set-up, sharpness, gamma, economy mode, OSD language, OSD position, OSD time out, signal select, volume
Driver	Windows 95 / 98 / 2000 / ME / XP
Ergonomics	TCO '03, TÜV-Ergonomics
Safety	TÜV GS, FCC-B, UL / C-UL, CE, VCCI-B, GOST-R, CCC, CB
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	max. 40 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	370.5 x 381 x 210 mm
Weight	4.1 kg
Aspect ratio	5 : 4

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.