



### A height adjustable 32" IPS Panel Technology monitor featuring WQHD resolution

The ProLite XB3270QS-B5 is a 31.5" screen featuring an IPS panel and WQHD (2560x1440) resolution, delivering both excellent colour performance with wide viewing angles and noticeably sharper images, which is ideal for productivity solutions, demanding office and financial applications. The 150mm height-adjustable stand ensures you can adjust the screen position to your preferences, and the flicker-free panel with blue light reducer function reduces eye fatigue.



WQHD

With true WQHD 2560 x 1440p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen, i.e. over 76% more in comparison to a 1920 x 1080 monitor.



IPS Technology

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

## 01 DISPLAY CHARACTERISTICS

|                     |   |
|---------------------|---|
| Diagonal            | 31.5", 80cm   |
| Panel               | IPS Panel Technology LED, matte finish                                |
| Native resolution   | 2560 x 1440 @60Hz (3.7 megapixel WQHD)                                |
| Aspect ratio        | 16:9  |
| Panel brightness    | 250 cd/m <sup>2</sup>   |
| Static contrast     | 1200:1  |
| Advanced contrast   | 80M:1   |
| Response time (GTG) | 4ms   |
| Viewing zone        | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support      | 1.07B 10bit (8bit + Hi-FRC) (sRGB:100%, NTSC: 72%)                    |
| Horizontal Sync     | 30 - 90kHz  |
| Viewable area W x H | 698.1 x 392.7mm, 27.5 x 15.5"   |
| Pixel pitch         | 0.273mm   |
| Colour              | matte, black  |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                     |                                     |
|---------------------|-------------------------------------|
| Signal input        | DVI x1<br>HDMI x1<br>DisplayPort x1 |
| HDCP                | yes                                 |
| Headphone connector | yes                                 |

## 03 FEATURES

|                    |  |
|--------------------|--|
| Blue light reducer | yes  |
| Flicker free       | yes  |
| Extra              | i-Style colour   |
| OSD languages      | EN, DE, FR, IT, RU, JP, CZ, NL, PL   |
| Control buttons    | Power, Menu, Scroll up/ Volume, Scroll down/ Eco, Input/ Exit  |
| User controls      | picture (picture format, brightness, contrast, black tuner, sharpness, overdrive, ACR, Eco, X-Res technology), colour (warm, normal, cool, user colour, i-Style colour, blue light reducer), input select, audio (volume, mute, audio input), language, OSD (H. position, V. position, background, time out), setup menu (HDMI RGB range, logo, LED, auto power off, memory recall, information) |
| Speakers           | 2 x 3W   |
| Convenience        | Kensington-lock™ prepared, DDC2B, Mac OSX  |

## 04 MECHANICAL

|                              |                          |
|------------------------------|--------------------------|
| Display position adjustments | height, swivel, tilt     |
| Height adjustment            | 150mm                    |
| Swivel stand                 | 90°; 45° left; 45° right |
| Tilt angle                   | 22° up; 3° down          |
| VESA mounting                | 100 x 100mm              |
| Cable management system      | yes                      |

## 05 ACCESSORIES INCLUDED

Cables power, HDMI, DP

Other quick start guide, safety guide

## 06 POWER MANAGEMENT

Power supply unit internal

Power supply AC 100 - 240V, 50/60Hz

Power usage 35W typical, 0.5W stand by

## 07 SUSTAINABILITY

Regulations CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369) F

REACH SVHC above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D 726 x 446 (596) x 245.5mm

Box dimensions W x H x D 810 x 176 x 510mm

Weight (without box) 8.6kg

Weight (with box) 11.6kg

EAN code 4948570121328



